

SOLIDEAL[®]

MAGNUM

RESILIENTS



SOLIDEAL[®]

SOLID CONSTRUCTION:

- The industry's premier resilient tire
- Great stability and driving comfort
- Latest construction techniques

DIFFERENT SOLUTIONS:

- ELCON compounds for electro-static charging problems
- Grey Non-Marking
- Grey Non-Marking Walnut for usage in wet and slippery environments
- Patented only anti-static non-marking tire in the world



solideal.com



| TIRE SIZE | AVAILABLE RIM WIDTHS | SECTION WIDTH +/- 2% [MM] | O.D. +/- 0.5% [MM] | REFERENCE LOAD (STEERING WHEEL AT 25 KM/H) [KG] |
|-------------------------|----------------------|---------------------------|--------------------|---|
| 3.00 - 4 | 2.1 / 2.5 | 84 | 251 | 195 |
| 4.00 - 4 | 2.1/ 2.5 | 96 | 307 | 410 |
| 4.00 - 8 | 3 | 103 | 410 | 730 |
| 5.00 - 8 | 3 / 3.25 | 122 | 450 | 1090 |
| 15X4 1/2-8 (125/75-8) | 3 / 3.25 | 114 | 376 | 800 |
| 16 X 6 - 8 (150/75-8) | 4.33 | 150 | 412 | 1150 |
| 18 X 7 - 8 (180/70-8) | 4.33 | 157 | 454 | 1650 |
| 5.00 - 9 | 3.5 | 129 | 487 | 1110 |
| 6.00 - 9 | 4 | 138 | 523 | 1450 |
| 7.00 - 9 | (5) | | | |
| 21 X 8 - 9 (200/75-9) | 6 | 187 | 517 | 2120 |
| 140 / 55 - 9 | 4 | 130 | 379 | 900 |
| 6.50 - 10 | 5 | 162 | 566 | 1800 |
| 7.50 - 10 | 5 / 5.5 | 180 / 185 | 631 | 2360 |
| 23 X 9 - 10 (225/75-10) | 6.5 | 204 | 583 | 2650 |
| 200/50 - 10 | 6.5 | 191 | 461 | 1900 |
| 7.00 - 12 | 5 | 172 | 652 | 2240 |
| 8.25 - 12 | 5 | 187 | 723 | 2645 |
| 23X10-12 (250/60-12) | 8 | 234 | 586 | 2900 |

| TIRE SIZE | AVAILABLE RIM WIDTHS | SECTION WIDTH +/- 2% [MM] | O.D. +/- 0.5% [MM] | REFERENCE LOAD (STEERING WHEEL AT 25 KM/H) [KG] |
|-------------------------|----------------------|---------------------------|--------------------|---|
| 27X10 - 12 (250/25-12) | 8 | 248 | 680 | 3000 |
| 150/100 - 13 (23x5) | 3.75 | 146 | 621 | 1320 |
| 6.00 - 15 | 4.5SDC | 160 | 698 | 2095 |
| 7.00 - 15 | 5.5 / 6 | 179 | 729 | 2725 |
| 7.50 - 15 | 5.5 / 6 / 6.5 | 199 | 752 | 3000 |
| 8.25 - 15 | 5.5 / 6 / 6.5 | 212 | 813 | 3650 |
| 28 X 9 - 15 (225/75-15) | 7 | 218 | 687 | 2900 |
| 350/50 - 15 | 9.75 | 295 | 712 | 4250 |
| 250 - 15 (250/70-15) | 7 / 7.5 | 225 | 716 | 3650 |
| 300 - 15 (315/70-15) | 8 | 257 | 815 | 4500 |
| 310 - 15 EW | 8V | 312 | 819 | 4750 |
| 355/65 - 15 | 9.75 | 312 | 819 | 6000 |
| 10.00 - 20 | 6.5 / 7 / 7.5/8 | 255 | 1035 | 4875 |
| 11.00 - 20 | 7.5 / 8 | 256 | 1060 | 5450 |
| 12.00 - 20 | 8 / 8.5 | 283 | 1090 | 6300 |
| 14.00 - 24 | 10 | 333 | 1320 | 9250 |
| 14.00 - 25 | 11.25 | 383 | 1334 | 10400 |
| 16.00 - 25 | 11.25 | 416 | 1445 | 12500 |

3.5: tire is available in normal and quick type 3.5: tire is available in normal only 3.5: tire is available in quick type only (): planned availability

Distributed By:



SOLIDEAL[®]